Oct 19, 01 15:04 **2001abs_text.txt** Page 1/1

Using MOLA Data to Improve Earth-based Radar Scattering Model Retrievals

Haldemann, A F albert@shannon.jpl.nasa.gov JPL, Caltech, M/S 238~420, Pasadena, CA 91109-8099 United States

Larsen, K W
Dept Earth and Planetary Sciences, Washington University, St. Louis, MO 63130
United States

Jurgens, R F JPL, Caltech, M/S 238-420, Pasadena, CA 91109-8099 United States

Slade, M A JPL, Caltech, M/S 238-420, Pasadena, CA 91109-8099 United States

Anderson, F S JPL, Caltech, M/S 238-420, Pasadena, CA 91109-8099 United States

Arvidson, R E
Dept Earth and Planetary Sciences, Washington University, St. Louis, MO 63130
United States

The Goldstone Solar System Radar (GSSR) has successfully collected radar echoes from the surface of Mars for some 30 years now. These data have been used in support of landing site selection and certific ation for Viking, Pathfinder, and the 2003 Mars Exploration Rovers. A recent re-analysis of the entire radar dataset availa ble brought to light a shortcoming of previous analyses. The technique used to date to fit the Hagfors scattering mode 1 to the radar echoes did not account for local slopes. In fact, it fails to fit a model to slopes over about 3 degrees, a nd gives good fits for regions with slopes less than about 1 degree. While landing sites are all in flat regions, understan ding the surface roughness on the flanks of Martian volcanos would be of significant interest. Generally the signal-to-noise of the radar echoes is insufficient to cleanly fit a fourth parameter, east-west slope, in addition to the parameters o f range, reflectivity and roughness. The MOLA topography offers an elegant solution. We will report on our study of the impro vement in scattering model fitting at the

meeting.