

Solid Earth Tide Modeling in VLBI

C.J. Naudet, C.S. Jacobs, O.J. Sovers, (Jet Propulsion Laboratory, California Institute of Technology, Pasadena, CA 91109;)

Over the last decade advances in Very Long Baseline Interferometry (VLBI) have produced baseline lengths with formal precisions as low as 6mm on 8,000 km baselines. The present IERS standards recommend a solid tide model based on the work of Wahr. This model assumes an elliptical, rotating, elastic, and oceanless Earth to obtain the calculated frequency dependence of the solar-moon-earth tidal potential. However, the standards retain only the largest frequency dependent term (the K1) ignoring terms that cause displacements of less than 5 mm. We have implemented Wahr's model including terms greater than half millimeter in the radial dimension. This includes the frequency dependence of the next six dominant Love numbers, such as O1, P1 and Ps1. These corrections are estimated to cause displacements of 1-5 mm. In addition, we have studied the effect of using the improved free core nutation period of Herring and Dong. These effects are investigated by analyzing the Deep Space Network's VLBI data (1978 to 1993). We will discuss the effect of the improved calculation on the scatter of the baseline lengths and on UTPM amplitudes at the diurnal and semi-diurnal frequencies.

1. 1994 Spring Meeting

2. 001300535

3. (a) C.J. Naudet  
MS 238-700  
Jet Propulsion Lab.  
4800 Oak Grove Dr.  
Pasadena, CA 91109

(t) Tel: 818-354-2053

(c) Fax: 818-393-4965

4. G (G02)

5. (a) None

(b) 1209 Crustal Movements  
8155 Plate Motions

6. None

7. None

8. Charge \$60.00 to Visa Card  
4019-0125-9803-5935 exp 9/95

9. C

10. None

11. No