

Superconducting Hot-Electron Bolometer Mixers at 0.5 Terahertz*

A. SKALARE, W. R. MCGRATH, B. BUMBLE, H. G. LUDUC, Jet Propulsion Laboratory, Pasadena, CA USA, P. J. BURKE, A. A. VERHEIJEN, D. E. PROBER, Yale University, New Haven, CT USA - Superconducting hot electron bolometer mixers are an interesting option for low noise astronomical receivers at sub-millimeter wavelengths, particularly at frequencies higher than 1 THz. The reason is that the bolometers should not suffer from the same performance degradation above the superconducting energy gap frequency as is observed in SIS mixers. However, the bolometers have a limited intermediate frequency bandwidth due to the finite time required to cool the hot electrons. We are investigating a short (<0.5 micron) niobium microbridge bolometer where the main cooling mechanism is expected to be out-diffusion of hot electrons into the surrounding normal-metal gold leads, rather than phonon emission. This out-diffusion process leads to predicted intermediate frequencies as high as 4 GHz. Initial measurements using a coherent source and a waveguide receiver have confirmed mixing in the device at a local oscillator frequency of 528 GHz and with an intermediate frequency of 1.4 GHz.

* This research was supported by NASA/OACT, BMDO/ISTO, NASA NAGW-3879 and a Connecticut High Technology Fellowship.

Presort Category: I-5 (Mixers)

Registrant: Anders Skalare, W.R. McGrath

Correspondence Author: Anders Skalare
Mail Stop 168-314
Jet Propulsion Laboratory
4800 Oak Grove Dr.
Pasadena, CA 91109

Tel: (818)354-9383

Fax: (818)393-4683

Telex:

ii-mail: anders@lolita.jpl.nasa.gov

Preference: Oral presentation