

Legacy of the Asteroid Redirect Robotic Mission (ARRM)

IEPC-2017-031

*Presented at the 35th International Electric Propulsion Conference
Georgia Institute of Technology • Atlanta, Georgia • USA
October 8 – 12, 2017*

John R. Brophy¹
*Jet Propulsion Laboratory, California Institute of Technology
Pasadena, CA 91190, USA*

NASA's proposed Asteroid Redirect Robotic Mission (ARRM) began with the recognition in a 2010 NASA study that emerging high-power solar electric propulsion technology could be used to rendezvous with, capture, and return an entire, very small (~10,000 kg), near Earth asteroids to the International Space Station. A 2011 workshop by the Keck Institute for Space Studies (KISS) extended the earlier NASA study to asteroid masses of order 500,000 kg by returning them to cislunar space. Subsequent detailed NASA studies in 2013-2014 confirmed the feasibility of this concept. This led to the establishment of the Asteroid Redirect Mission program that consisted of a robotic mission to return multiple tons of asteroid material to cislunar space and a crewed mission to rendezvous with the robotic vehicle, perform two extra vehicular activities (EVAs), collect samples of the asteroid material, and return this material to Earth. Implementation of ARRM got midway through Phase B before being cancelled in April 2017. Although ARRM was cancelled, it has left a near-term legacy of positive impacts to the human spaceflight community, the planetary defense community, the deep space science community, and asteroid mining interests.

I. Introduction

THE idea to exploit the natural resources of asteroids is older than the space program [1]. Numerous studies have identified and evaluated the benefits and challenges of exploiting the natural resources of near-Earth asteroids, see for example [2-13]. These studies and others identify three generic approaches for mining asteroids: 1) Mine and process the material at the asteroid and return only the processed material; 2) Mine the asteroid and return the raw material for processing; 3) Return an entire small asteroid to a more convenient location for processing. For all of these approaches, transportation is a major challenge, both to rendezvous with the target asteroid, as well as to return the asteroid material (processed or unprocessed) to the desired point of use. To address the transportation problem, most conceptual studies of asteroid mining assumed the use of reaction mass that, in one form or another, is obtained from the asteroid itself.

This situation changed significantly beginning with a 2010 NASA study. This study recognized that near-term advances in high-power solar electric propulsion (SEP) could make it feasible to capture and return an entire small near-Earth asteroid (NEA), with a diameter of about 2 m and a mass of roughly 10,000 kg, to the International Space Station [14], without using reaction mass obtained from the asteroid itself. This approach promised to greatly reduce the cost and complexity of returning large amounts (10's to 100's of tons) of asteroid material to cislunar space. The 2010 NASA study was followed by a feasibility study conducted at the Keck Institute for Space Studies (KISS) which investigated two options for asteroid retrieval [15]. The first option considered the capture and return to cislunar space of an entire small near-Earth asteroid with a diameter of approximately 8 m and a mass of order 500,000 kg. The other option examined the feasibility of extracting a boulder several meters in diameter from the surface of a larger NEA and returning this boulder to cislunar space. A key feature of both options was to create a high-value target in cislunar space for a human mission beyond low Earth orbit for the first time since 1972. NASA considered the KISS concept sufficiently interesting that it sponsored follow-on studies to investigate the feasibility in more detail. These studies,

¹ Engineering Fellow, Propulsion, Thermal and Materials Engineering Section, John.R.Brophy@jpl.nasa.gov.

which focused primarily on the concept to capture and return an entire ~8-m diameter asteroid, confirmed that this mission concept did indeed look feasible [16-24]. In the course of subsequent formulation studies, NASA ultimately decided that picking a multi-meter diameter boulder off a larger NEA would develop a broader range of technologies extensible to future human exploration of Mars and its moons [25]. This mission concept became known as the Asteroid Redirect Robotic Mission (ARRM). In parallel with this selection, NASA established the Asteroid Redirect Mission (ARM) Program consisting of two missions, ARRM and a joint human/robotic mission called the Asteroid Redirect Crewed Mission (ARCM). ARRM would use a robotic spacecraft with a high-power SEP system to rendezvous with a near-Earth asteroid, land on the surface, extract a 2-6 m diameter boulder from the surface, and return that boulder to cislunar space. ARCM would have an astronaut crew in the Orion vehicle rendezvous with and dock to the ARRM vehicle, conduct two extra vehicular activities (EVAs) to obtain samples of the boulder, and return those samples to Earth.

Implementation of ARRM was led by the Jet Propulsion Laboratory (JPL) from 2014 through mid. 2017 with major participation by Glenn Research Center, Goddard Space Flight Center, Langley Research Center, Johnson Space Center, and Kennedy Space Center. The ARRM Pre-Phase A/Phase A study was conducted from June 2014 through July 2016. Following a successful Key Decision Point-B review ARRM entered Phase B in August 2016. Approximately mid-way through Phase B, the ARRM activity was terminated by NASA in April 2017. Even though the mission will not be implemented, its existence impacted a significant range of NASA's interests. While its long-term legacy remains uncertain, the short-term legacy of the Asteroid Redirect Mission is highlighted briefly below.

II. ARRM Impacts

The ARM Project impacted a number of NASA interests including high-power solar electric propulsion, human spaceflight, deep space robotic missions, in situ resource utilization, and planetary defense.

A. High-Power Solar Electric Propulsion Technology

One of the most important aspects of ARRM would have been the development and demonstration of a high-power solar electric propulsion system in deep space that would serve as a risk-reduction stepping-stone toward the development of multi-hundred kilowatt systems needed to support human missions to Mars. Numerous Mars mission concept studies spanning decades have identified the need for very high-power SEP systems (100's of kilowatts or greater). However, the highest power electric propulsion (EP) system flown in deep space to date is the 2.5-kW ion propulsion system on NASA's Dawn spacecraft. Building a multi-hundred kilowatt SEP system based on the Dawn experience would likely expose such a project to unacceptably high risk. Flight implementation of an intermediate step up in power would significantly mitigate this risk. Demonstration by ARRM of an electric propulsion system at a power level of 40 kW would be sixteen times the state of the art for deep space EP systems. Implementation of a hypothetical 200 kW EP system, such as might be needed for human Mars missions, would then only be a more manageable factor of five greater than the ARRM system. Thus, a 40-kW electric propulsion system for ARRM appeared to be a reasonable stepping-stone forward to higher power systems.

Throughout all of the early feasibility and formulation studies of the asteroid retrieval concept conducted by NASA, one thing remained constant, the robotic mission concept would use a 40-kW, Hall-thruster based SEP system. The fine details of this system changed over time. For example, the output voltage range for the solar array was the subject of significant trade studies and debate. The maximum thruster input power, the maximum thruster specific impulse, and the details of the throttle table all changed over time. But, the basic architecture which used a small number of high-power, high-specific impulse, magnetically-shielded Hall thrusters, with a total electric propulsion system input power of ~40 kW, remained constant. This was driven primarily by the assertion in the 2010 study [14] that a solar array with an output power of about 50 kW at 1 AU represented the best balance between implementation risk and pushing light-weight, deployable, solar array technology to higher power levels.

NASA's initial feasibility study in 2013 [22] considered launch readiness dates as early as 2017. Budget realities would result in the launch readiness date slipping approximately one year per year. At the time ARRM was terminated in 2017, the project was targeting a launch readiness date at the end of 2021. For launch dates in 2021 or later, a case could be made that 50 kW no longer represents the best stepping stone to multi-hundred kilowatt solar arrays projected to be needed to support human missions to Mars and that the ARRM spacecraft, or whatever replaces ARRM should target higher power solar arrays.

To support a launch readiness date at the end of 2021, NASA initiated the development of the required Hall thrusters along with their power processing units (PPUs) and xenon flow control assemblies (XCAs). A competitive procurement activity managed by GRC selected Aerojet Rocketdyne for this development with significant risk reduction activities performed in parallel at GRC and JPL. The high-power Hall thruster for ARRM was given the

name HERMeS (Hall Effect Rocket with Magnetic Shielding). Development of the thruster, PPU, and XCA are documented in numerous technical papers, see for example [26-50].

B. Human Spaceflight

Prior to ARRM, NASA intended to send astronauts to a near-Earth asteroid in the mid 2020s. In studying this concept it became clear to NASA that there were numerous difficulties that had the potential to significantly increase the cost of such a mission. These difficulties included lack of abort modes, vulnerability to solar flares, long flight times, and lack of resupply opportunities [51]. The ability to bring NEA's to cislunar space suggested that with respect to cost, complexity, risk, duration and resupply it may be better to bring these objects to the astronauts rather than send astronauts to a NEA, at least initially [51]. Such a mission would likely be significantly easier and less expensive than a mission to a NEA in its native orbit, but would still draw astronauts away from low-Earth orbit for the first time in more than 50 years. It would have transit times measured in days not months, abort-to-Earth times also measured in days not months, and it would put astronauts in contact with only the second extraterrestrial object in history (the Moon being the first).

A key feature of such a mission would be the experience NASA would gain from working out the requirements and procedures for a human crew to interact with a robotic spacecraft in deep space. Such experience would be valuable for potential future human missions to Mars, which almost certainly will involve a mix of interacting human and robotic vehicles.

A significant part of ARRM's near-term legacy on human spaceflight is the expanded recognition and understanding by the human spaceflight community of the benefits that high-power solar electric propulsion can provide for human missions to the Martian system. Prior to ARRM the benefits of high-power SEP for such missions was widely recognized within the electric propulsion community, but not as widely recognized outside of that community. ARRM and the mission studies that supported it and its extensibility to potential human missions to Mars changed this. A notable example of this is the so-called SEP/Chem hybrid architecture that combines the best features of high-power SEP with high-thrust chemical propulsion to reduce the overall flight times to those comparable to all-chemical propulsion architectures, while significantly reducing the initial mass in low-Earth orbit [61]. Significantly, this approach also reduces the overall mission risk, since the SEP/Chem hybrid vehicle could take all of the supplies and propellant necessary for the complete round-trip mission eliminating the need for a rendezvous with pre-positioned assets in Mars orbit in order to return to Earth.

Further impacts of ARRM on human spaceflight and low-thrust trajectory design are discussed in references [51-75].

C. Deep Space Robotic Missions

It has long been recognized that solar electric propulsion has the effect of making every launch vehicle better. That is, SEP can enable missions from smaller launch vehicles that would be impossible otherwise. Strange and Landau [69] have carried this concept to an extreme level, combining a 150-kW ARRM derived robotic vehicle with a Block 1a Space Launch System (SLS). The resulting performance is impressive as an example of what might be possible. Such a system is projected to be capable of delivering 12,200 kg to orbit around Jupiter in a flight time of just 3 years; 8,500 kg to orbit around Saturn in 5 years; 4,400 kg to orbit around Uranus in 9 years; or 4,500 kg to orbit around Neptune in 13 years.

D. Asteroid Mining

ARRM had a significant impact on multiple aspects of potential future asteroid mining activities as indicated by references [76-107]. Multiple asteroid retrieval studies by NASA from 2010 through 2014 confirmed the feasibility of a high-power SEP-based robotic vehicle to retrieve entire small asteroids with masses that are > 50X the mass of the SEP propellant. Return of hundreds of tons of asteroid mass to cislunar space enables asteroid mining equipment to stay relatively close to Earth. It also makes products derived from asteroidal materials available for relatively near-term space development in cislunar space [51]. While it is debatable what the most valuable near-term use of asteroid material will be, its use as radiation shielding to protect astronauts from galactic cosmic rays seems like a good candidate. Such an application would require lots of material, 100's to 1000's of tons, but would require little processing of this material.

Ultimately, asteroid mining will have to rely on asteroid-derived propellants to avoid the high cost of lifting propellants from Earth. Most concepts assume the use of water extracted from the asteroid as the source of this propellant for use either in solar thermal rockets or in LOX/H₂ systems. ARRM's legacy with high-power, magnetically-shielded Hall thrusters suggests another possible approach. Asteroids are extremely poor sources of the

inert gases typically used with Hall thrusters. However, asteroids are believed to have a significant amount of magnesium (~10 to 15%) and sulfur (~2 to 5%). Hall thrusters have been successfully operated on magnesium in the laboratory [108]. While no one has yet operated a Hall thruster on sulfur, it has a lower melting temperature than magnesium and a significantly lower temperature for the same vapor pressure. These features suggest that Hall thruster operation on sulfur may be easier than on magnesium. The low atomic mass of sulfur would enable high Isp operation in direct-drive systems with moderate solar array voltages [107].

E. Planetary Defense

Prior to ARRM, SEP was recognized as enabling or enhancing for most planetary defense techniques including kinetic impactors and gravity tractors [109]. A variation on the gravity tractor [110] is the so-called “enhanced” gravity tractor (EGT) in which the gravitational coupling between the asteroid and the spacecraft is enhanced by the spacecraft acquiring mass from the asteroid prior to the initiation of tractoring [111, 112]. The resulting higher coupling force in an enhanced gravity tractor system requires high-power SEP in order to provide the necessary thrust levels. ARRM, with its 40-kW SEP system would have been the first demonstration of a gravity tractor, and specifically would demonstrated the EGT technique on a 100-m class NEA.

During the ARRM development, however, it was recognized that a planetary defense technique sometimes referred to as ion beam deflection (IBD) would benefit significantly from the development of high-power SEP systems. This technique is under appreciated by the planetary defense community. Ion beam deflection works by directing a beam of high-energy ions into the surface of the threat object and transferring the momentum of the ions to the object through inelastic collisions [113-118]. This is conceptually similar to a kinetic impactor with the impinging ions taking the place of the impacting spacecraft, but with two important differences. First, an ion beam deflection system can be designed so that the ions impact the asteroid surface at speeds much greater than is practical for kinetic impactor. Second, the ions can impact in the direction most effective for deflection. Ion impact speeds of 70 km/s are readily achievable, which would be roughly four to five times the impact speed of a kinetic impactor spacecraft. The finite power levels for the IBD vehicle means the transfer of momentum is necessarily spread out over time, typically over a timescale of months to years.

NASA is mandated by Congress to discover and track all NEOs greater than 140 meters in diameter. At the completion of this survey, if nothing is found on a collision course with Earth, then the impact risk will be dominated by Tunguska-scale objects, i.e., objects that are tens of meters in diameter [119]. IBD is particularly well suited to the deflection of objects in the size range of 50 m to 100 m diameter. A high-power IBD vehicle (of order 100 kW) could likely deflect such objects in matter of months. For example, if asteroid hypothetical asteroid 2017 PDC (used in the 2017 Planetary Defense Conference exercise) was 100 m diameter with a density of 2 g/cm³, it would take only two months of IBD operations for a 160-kW IBD vehicle to deflect it by one Earth radius, assuming that deflection operations began 3.6 years before impact [118].

III. Conclusion

NASA’s ARM program, which consisted of a robotic mission (ARRM) and a crewed mission (ARCM) would have impacted a wide variety of NASA’s interests including: the demonstration of high-power solar electric propulsion at 16x the power level of the current state-of-the art for deep space electric propulsion systems; demonstration of precision landing on an airless body; demonstration of the ability to grasp, extract, and control a large non-cooperative object on the surface of an asteroid; demonstration of a planetary defense technique known as an enhanced gravity tractor; demonstration of the ability to transport a multi-ton payload through deep space; demonstration of joint operations with crewed and robotic vehicles; the return to Earth of large quantities of C-type asteroid material; human exploration beyond low-Earth orbit for the first time in more than 50 years; and human exploration of only the second extraterrestrial body in history.

Work related to ARM created a near-term legacy that includes: appreciation by the human spaceflight community of the benefits of high-power solar electric propulsion for human missions beyond low-Earth orbit; development of the SEP/Chem hybrid approach for human missions concepts to Mars that provide the mass savings of EP missions with the trip times comparable to all chemical propulsion missions; verification by multiple in depth studies of the feasibility of capturing and returning to cislunar space entire small near Earth asteroids; and emerging recognition by the planetary defense community of the potential benefits of high-power SEP for ion beam deflection of potentially hazardous asteroids in the size range of 50 to 100 m diameter.

Acknowledgments

The research described in this paper was carried out at the Jet Propulsion Laboratory, California Institute of Technology, under a contract with the National Aeronautics and Space Administration.

References

- ¹Tsiolkovskii, K., *The Exploration of Cosmic Space by Means of Rocket Propulsion*, published in Russia, 1903.
- ²O'Neill, G.K., "The Colonization of Space, *Physics Today*, 27 (9): 32-40, September 1974.
- ³O'Leary, B., "Mining the Apollo and Amor Asteroids, *Science*, 1977 Jul 22; 197 (4301): 363-6.
- ⁴O'Leary, B., Gaffey, M.J., Ross, D.J., and Salkeld, R., "Retrieval of Asteroidal Materials," in *NASA Ames Research Center Space Resources and Space Settlements*, p 173-189 (SEE N 79-32225 23-12).
- ⁵O'Leary, B.T., "Asteroid Prospecting and Retrieval," AIAA 79-1432, Fourth Princeton/AIAA Conference on Space Manufacturing Facilities, Princeton, NJ, May 14-17, 1979.
- ⁶O'Leary, B.T., "Mass Driver Retrieval of Earth-Approaching Asteroids," AIAA 77-528, Third Princeton/AIAA Conference on Space Manufacturing Facilities, Princeton, NJ, May 9-12, 1977.
- ⁷Pearson, J., "Asteroid Retrieval by Rotary Rocket," AIAA-80-0116, AIAA 18th Aerospace Sciences Meeting, Pasadena, CA, January 14-16, 1980.
- ⁸Singer, C.E., "Collisional Orbital Change of Asteroidal Materials," AIAA 79-1434, Fourth Princeton/AIAA Conference on Space Manufacturing Facilities, Princeton, NJ, May 14-17, 1979.
- ⁹Lewis, J. S., *Mining the Sky*, Helix Books, New York, 1996 2. Lewis, J. S., *Mining the Sky*, Helix Books, New York, 1996.
- ¹⁰Sonter, M.J., "The Technical and Economic Feasibility of Mining the Near-Earth Asteroids," presented at the 49th IAF Congress, Sept 28-Oct 2, 1998, Melbourne, Australia.
- ¹¹Ross, S.D., "Near-Earth Asteroid Mining," Space Industry Report, December 14, 2001.
- ¹²Rice, E.E, and Gustafson, R.J., "Review of Current Indigenous Space Resource Utilization (ISRU) Research and Development," AIAA-2000-1057, 38th Aerospace Sciences Meeting and Exhibit, 10-13 January 2000, Reno, NV.
- ¹³Erickson, K.R., "Optimal Architecture for an Asteroid Mining Mission: Equipment Details and Integration," AIAA 2006-7504, Space 2006, 19-21 September 2006, San Jose, CA.
- ¹⁴Brophy, J.R., et al., "Feasibility of Capturing and Returning Small Near-Earth Asteroids," IEPC-2011-277, Presented at the 32nd International Electric Propulsion Conference, Wiesbaden, Germany, September 11 – 15, 2011.
- ¹⁵Brophy, J.R., et al., "Asteroid Retrieval Feasibility Study," 2 April 2012, KISS Phase 1 Study Final Report, http://www.kiss.caltech.edu/study/asteroid/asteroid_final_report.pdf.
- ¹⁶Brophy, J.R., and Oleson, S., "Spacecraft Conceptual Design for Returning Entire Near-Earth Asteroids," AIAA 2012-4067, 48th AIAA/ASME/SAE/ASEE Joint Propulsion Conference & Exhibit and 10th International Energy Conversion Engineering Conference, Atlanta, Georgia, 29 July - 1 August 2012.
- ¹⁷Brophy, J.R., Frideman, L., and Culick, F., "Asteroid Retrieval Feasibility," presented at the IEEE Aerospace Conference, Big Sky, MT, 2012.
- ¹⁸Brophy, J.R. and Friedman, L., et al., "Returning an Entire Near-Earth Asteroid in Support of Human Exploration Beyond Low-Earth Orbit," GLEX-2012.11.1.7x12334.
- ¹⁹Brophy, J., Culick, F., Dimotakis, P., and Friedman, L., "Project 5S: A Safe Stepping Stone into the Solar System," IAC-12,A5,4,11,x13356, 63rd International Astronautical Congress, Naples, Italy, 2012.
- ²⁰Brophy, J.R. and Muirhead, B. "Near-Earth Asteroid Retrieval Mission (ARM) Study," IEPC-2013-82, Presented at the 33rd International Electric Propulsion Conference, Washington, DC, October 6 – 10, 2013.
- ²¹Brophy, J.R., Gershman, R., and Friedman, L., "Asteroid-Retrieval—A New Synergy between Robotic and Human Exploration Missions," presented at the IEEE Aerospace Conference, Big Sky, MT, 2013.
- ²²Muirhead, B.K. and Brophy, J.R., "Asteroid Redirect Robotic Mission Feasibility Study," presented at the IEEE Aerospace Conference, Big Sky, MT, 2014.
- ²³Brophy, J.R., "Technology for a Robotic Asteroid Redirect Mission," presented at the IEEE Aerospace Conference, Big Sky, MT, 2014.
- ²⁴Brophy, J., "Technology for a Robotic Asteroid Redirect Mission and Its Extensibility to Future Human and Robotic Missions," presented at the IEEE Aerospace Conference, Big Sky, MT, 2015.
- ²⁵Mazanek, D.D., et al., "Asteroid Redirect Robotic Mission: Robotic Boulder Capture Option Overview," AIAA 2014-4432, AIAA SPACE 2014 Conference and Exposition. San Diego, CA, 2014.

ARRM Electric Propulsion Technology

- ²⁶Kamhawi, H., et al., "Overview of the Development of the Solar Electric Propulsion Technology Demonstration Mission 12.5-kW Hall Thruster," AIAA 2014-3898, 50th AIAA/ASME/SAE/ASEE Joint Propulsion Conference. Cleveland, OH, 2014.
- ²⁷McGuire, M.L., et al., "Concept designs for NASA's Solar Electric Propulsion Technology Demonstration Mission," AIAA 2014-3717, 50th AIAA/ASME/SAE/ASEE Joint Propulsion Conference. Cleveland, OH, 2014.
- ²⁸Mikellides, I.G., Lopez Ortega, A. and Jorns, B. "Assessment of Pole Erosion in a Magnetically Shielded Hall Thruster," AIAA 2014-3897, 50th AIAA/ASME/SAE/ASEE Joint Propulsion Conference. Cleveland, OH, 2014.

- ²⁹Hofer, R.R. and Anderson, J.R., “Finite Pressure Effects in Magnetically Shielded Hall Thrusters,” AIAA 2014-3709, 50th AIAA/ASME/SAE/ASEE Joint Propulsion Conference. Cleveland, OH, 2014.
- ³⁰Huang, W., et al., “Non-Contact Thermal Characterization of NASA’s 12.5-kW Hall Thruster,” AIAA 2015-3920, 51st AIAA/SAE/ASEE Joint Propulsion Conference. Orlando, FL, 2015.
- ³¹Shastri, R., Huang, W. and Kanhawi, H. “Near-Surface Plasma Characterization of the 12.5-kW NASA TDU1 Hall Thruster,” AIAA 2015-3919, 51st AIAA/SAE/ASEE Joint Propulsion Conference. Orlando, FL, 2015.
- ³²Pinero, L., et al., “Development of High-Power Hall Thruster Power Processing Units at NASA GRC,” AIAA 2015-3921, 51st AIAA/SAE/ASEE Joint Propulsion Conference. Orlando, FL, 2015.
- ³³Herman, D.A., et al., “The Ion Propulsion System for the Asteroid Redirect Robotic Mission,” AIAA 2016-4824, 52nd AIAA/SAE/ASEE Joint Propulsion Conference. Salt Lake City, UT, 2016.
- ³⁴Hofer, R.R., et al., “The 12.5 kW Hall Effect Rocket with Magnetic Shielding (HERMeS) for the Asteroid Redirect Robotic Mission,” AIAA 2016-4825, 52nd AIAA/SAE/ASEE Joint Propulsion Conference. Salt Lake City, UT, 2016.
- ³⁵Conversano, R.W., et al., “Performance Comparison of the 12.5 kW HERMeS Hall Thruster Technology Demonstration Units,” AIAA 2016-4827, 52nd AIAA/SAE/ASEE Joint Propulsion Conference. Salt Lake City, UT, 2016.
- ³⁶Williams, G., et al., “2000-hour Wear-Testing of the HERMeS Thruster,” AIAA 2016-5025, 52nd AIAA/SAE/ASEE Joint Propulsion Conference. Salt Lake City, UT, 2016.
- ³⁷Myers, J.L., et al., “Hall Thruster Thermal Modeling and Test Data Correlation,” AIAA 2016-4535, 52nd AIAA/SAE/ASEE Joint Propulsion Conference. Salt Lake City, UT, 2016.
- ³⁸Yanes, N., et al., “Ion Acoustic Turbulence and Ion Energy Measurements in the Plume of the HERMeS Thruster Hollow Cathode,” AIAA 2016-5028, 52nd AIAA/SAE/ASEE Joint Propulsion Conference. Salt Lake City, UT, 2016.
- ³⁹Goebel, D.M. and Polk, J.E., “Lanthanum Hexaboride Hollow Cathode Performance and Wear Testing for the Asteroid Redirect Mission Hall Thruster,” AIAA 2016-4835, 52nd AIAA/SAE/ASEE Joint Propulsion Conference. Salt Lake City, UT, 2016.
- ⁴⁰Reilly, S.W., Sekerak, M.J. and Hofer, R.R., “Transient Thermal Analysis of the 12.5 kW HERMeS Hall Thruster,” AIAA 2016-5024, 52nd AIAA/SAE/ASEE Joint Propulsion Conference. Salt Lake City, UT, 2016.
- ⁴¹Huang, W., Kanhawi, H. and Haag, T., “Plasma Oscillation Characterization of NASA’s HERMeS Hall Thruster via High Speed Imaging,” AIAA 2016-4829, 52nd AIAA/SAE/ASEE Joint Propulsion Conference. Salt Lake City, UT, 2016.
- ⁴²Gilland, J.H., et al., “Carbon Back Sputter Modeling for Hall Thruster Testing,” AIAA 2016-4941, 52nd AIAA/SAE/ASEE Joint Propulsion Conference. Salt Lake City, UT, 2016.
- ⁴³Sarver-Verhey, T.R., et al., “Hollow Cathode Assembly Development for the HERMeS Hall Thruster,” AIAA 2016-5026, 52nd AIAA/SAE/ASEE Joint Propulsion Conference. Salt Lake City, UT, 2016.
- ⁴⁴Kanhawi, H., et al., “Facility Pressure Effects, and Stability Characterization Tests of NASA’s 12.5-kW Hall Effect Rocket with Magnetic Shielding Thruster,” AIAA 2016-4826, 52nd AIAA/SAE/ASEE Joint Propulsion Conference. Salt Lake City, UT, 2016.
- ⁴⁵Huang, W., Kanhawi, H. and Haag, T., “Facility Effect Characterization Test of NASA’s HERMeS Hall Thruster,” AIAA 2016-4828, 52nd AIAA/SAE/ASEE Joint Propulsion Conference. Salt Lake City, UT, 2016.
- ⁴⁶Mikellides, I.G., et al., “Hall2De Simulations with a First-principles Electron Transport Model Based on the Electron Cyclotron Drift Instability,” AIAA 2016-4618, 52nd AIAA/SAE/ASEE Joint Propulsion Conference. Salt Lake City, UT, 2016.
- ⁴⁷Peterson, P.Y., et al., “NASA’s HERMeS Hall Thruster Electrical Configuration Characterization,” AIAA 2016-5027, 52nd AIAA/SAE/ASEE Joint Propulsion Conference. Salt Lake City, UT, 2016.
- ⁴⁸Jorns, B., et al., “Mechanisms for Pole Piece Erosion in a 6-kW Magnetically-Shielded Hall Thruster,” AIAA 2016-4839, 52nd AIAA/SAE/ASEE Joint Propulsion Conference. Salt Lake City, UT, 2016.
- ⁴⁹Jorns, B., Lopez Ortega, A. and Mikellides, I.G., “First-principles Modelling of the IAT-driven Anomalous Resistivity in Hollow Cathode Discharges I: Theory,” AIAA 2016-4626, 52nd AIAA/SAE/ASEE Joint Propulsion Conference. Salt Lake City, UT, 2016.
- ⁵⁰Lopez Ortega, A., Mikellides, I.G. and Jorns, B. “First-principles modeling of the IAT-driven anomalous resistivity in hollow cathode discharges II: Numerical simulations and comparison with measurements,” AIAA 2016-4627, 52nd AIAA/SAE/ASEE Joint Propulsion Conference. Salt Lake City, UT, 2016.

ARM and Human Spaceflight

- ⁵¹Globus, A., et al., “A Comparison of Astronaut Near-Earth Object Missions,” AIAA 2012-5328, AIAA SPACE 2012 Conference & Exposition. Pasadena, California, 2012.
- ⁵²Condon, G.L. and Williams, J., “Asteroid Redirect Crewed Mission Nominal Design and Performance,” AIAA 2014-1696, SpaceOps 2014 Conference. Pasadena, CA, 2014.
- ⁵³Williams, J. and Condon, G.L., “Contingency Trajectory Planning for the Asteroid Redirect Crewed Mission,” AIAA 2014-1697, SpaceOps 2014 Conference. Pasadena, CA, 2014.
- ⁵⁴Blanco, R.A., “Asteroid Redirect Crewed Mission Space Suit and EVA System Architecture Trade Study, AIAA 2014-1717, SpaceOps 2014 Conference. Pasadena, CA, 2014.
- ⁵⁵Williams, J. and Condon, G.L., “Contingency Trajectory Planning for the Asteroid Redirect Crewed Mission,” AIAA 2014-1697, SpaceOps 2014 Conference. Pasadena, CA, 2014.

⁵⁶Bacon, C., et al., “Achieving Supportability on Exploration Missions with In-Space Servicing,” AIAA 2015-4478, AIAA SPACE 2015 Conference and Exposition. Pasadena, California, 2015.

⁵⁷Duggan, M., Engle, J.M. and Moseman, T.A., “A Resilient Cislunar Spacecraft Architecture to Support Key Mars Enabling Technologies and Operation Concepts,” AIAA 2016-5217, AIAA SPACE 2016. Long Beach, California, 2016.

⁵⁸Smitherman, D.V., “Habitation Concepts for Human Missions Beyond Low-Earth-Orbit,” AIAA 2016-5216, AIAA SPACE 2016. Long Beach, California, 2016.

Human missions to Mars

⁵⁹Lopez, P., et al., “Extensibility of Human Asteroid Mission to Mars and Other Destinations,” AIAA 2014-1699, SpaceOps 2014 Conference. Pasadena, CA, 2014.

⁶⁰Price, H.W., et al., “Human Missions to Mars Orbit, Phobos, and Mars Surface Using 100-kWe-Class Solar Electric Propulsion,” AIAA 2014-4436, AIAA SPACE 2014 Conference and Exposition. San Diego, CA, 2014.

⁶¹Chai, P., Merrill, R.G. and Qu, M. “Mars Hybrid Propulsion System Trajectory Analysis, Part I: Crew Missions,” AIAA 2015-4443, AIAA SPACE 2015 Conference and Exposition. Pasadena, California, 2015.

⁶²Chai, P., Merrill, R.G. and Qu, M. “Mars Hybrid Propulsion System Trajectory Analysis, Part II: Cargo Missions,” AIAA 2015-4444, AIAA SPACE 2015 Conference and Exposition. Pasadena, California, 2015.

⁶³Mercer, C.R., McGuire, M. and Oleson, S.R., “Solar Electric Propulsion Concepts for Human Space Exploration,” AIAA 2015-4521, AIAA SPACE 2015 Conference and Exposition. Pasadena, California, 2015.

⁶⁴Csank, J., Aulisio, M.V and Loop, B. “150 kW Class Solar Electric Propulsion Spacecraft Power Architecture Model,” AIAA 2017-4872, 15th International Energy Conversion Engineering Conference. Atlanta, GA, 2017.

⁶⁵Rodgers, E., et al., “Graphical Visualization of Human Exploration Capabilities,” AIAA 2016-5422, AIAA SPACE 2016. Long Beach, California, 2016.

⁶⁶Cameron, J.M., et al., “DSEDS: Multi-mission Flight Dynamics Simulator for NASA Missions,” AIAA 2016-5421, AIAA SPACE 2016. Long Beach, California, 2016.

⁶⁷Smitherman, D.V and Griffin, B.N., “Habitat Concepts for Deep Space Exploration,” AIAA 2014-4110, AIAA SPACE 2014 Conference and Exposition. San Diego, CA, 2014.

⁶⁸Manzella, D.H. and Hack, K., “High-Power Solar Electric Propulsion for Future NASA Missions,” AIAA 2014-3718, 50th AIAA/ASME/SAE/ASEE Joint Propulsion Conference. Cleveland, OH, 2014.

Trajectory Design

⁶⁹Strange, N.J. and Landau, D., “Outer Planet Flagship Missions with ARM-derived Electric Propulsion Stage,” presented at the Outer Planets Assessment Group (OPAG) meeting, NASA Ames, February 2015.

⁷⁰Merrill, R.G, et al., “Interplanetary Trajectory Design for the Asteroid Robotic Redirect Mission Alternate Approach Trade Study,” AIA 2014-4457, AIAA/AAS Astrodynamics Specialist Conference. San Diego, CA, 2014.

⁷¹Bezrouk, C.J. and Parker, J. “Long Duration Stability of Distant Retrograde Orbits,” AIAA 2014-4424, AIAA/AAS Astrodynamics Specialist Conference. San Diego, CA, 2014.

⁷²Perozzi, E. and Marò, S., “The Accessibility of the Near-Earth Asteroids, Asteroid and Space Debris Manipulation: Advances from the Stardust Research Network,” 71-82, 10.2514/5.9781624103247.0071.0082

⁷³Misra, G. and Sanyal, A.K., “Analysis of Orbit-Attitude Coupling of Spacecraft Near Small Solar System Bodies,” AIAA 2015-1777, AIAA Guidance, Navigation, and Control Conference. Kissimmee, Florida, 2015.

⁷⁴Mingotti, G., Sanchez, J. and McInnes, C. “Low Energy, Low-Thrust Capture of Near Earth Objects in the Sun-Earth and Earth-Moon Restricted Three-Body Systems,,” AIAA 2014-4301, AIAA/AAS Astrodynamics Specialist Conference. San Diego, CA, 2014.

⁷⁵Guzzetti, D., Bosanac, N. and Howell, K.C. “A Framework for Efficient Trajectory Comparisons in the Earth-Moon Design Space,” AIAA 2014-4110, AIAA/AAS Astrodynamics Specialist Conference. San Diego, CA, 2014.

Asteroid/boulder Capture & ProxOps

⁷⁶Gefke, G.G, et al., “Increasing Baseline Robot Arm Boulder Extraction Robustness for ARRM,” AIAA 2017-5119, AIAA SPACE and Astronautics Forum and Exposition. Orlando, FL, 2017.

⁷⁷Englander, J., “Mars, Phobos, and Deimos Sample Return Enabled by ARRM Alternative Trade Study Spacecraft,” AIAA 2014-4354, AIAA/AAS Astrodynamics Specialist Conference. San Diego, CA, 2014.

⁷⁸Falcone, G., et al., “Attitude Control of the Asteroid Redirect Robotic Mission Spacecraft with a Captured Boulder,” AIAA-2016-5645, AIAA/AAS Astrodynamics Specialist Conference. Long Beach, California, 2016.

⁷⁹Reed, B.B, et al., “The “Master Enabler” - In-Orbit Servicing,” AIAA 2015-4645, AIAA SPACE 2015 Conference and Exposition. Pasadena, California, 2015.

⁸⁰Ticker, R.L, Cepollina, F. and Reed, B.B, “NASA’s In-Space Robotic Servicing,” AIAA 2015-4644, AIAA SPACE 2015 Conference and Exposition. Pasadena, California, 2015.

⁸¹Belbin, S.P. and Merrill, R.G, “Boulder Capture System Design Options for the Asteroid Robotic Redirect Mission Alternate Approach Trade Study,” AIAA 2014-4434, AIAA SPACE 2014 Conference and Exposition. San Diego, CA, 2014.

- ⁸²Gefke, G., et al., “Advances in Robotic Servicing Technology Development,” AIAA 2015-4426, AIAA SPACE 2015 Conference and Exposition. Pasadena, California, 2015.
- ⁸³Reeves, D.M., et al., “Proximity Operations for the Robotic Boulder Capture Option for the Asteroid Redirect Mission,” AIAA 2014-4433, AIAA SPACE 2014 Conference and Exposition. San Diego, CA, 2014.
- ⁸⁴Strange, N.J., et al., “Identification of Retrievable Asteroids with the Tisserand Criterion,” AIAA 2014-4458, AIAA/AAS Astrodynamics Specialist Conference. San Diego, CA, 2014.
- ⁸⁵Shen, H., Roithmayr, C. and Cornelius, D.M., “Controlled Ascent from the Surface of an Asteroid,” AIAA 2014-4303, AIAA/AAS Astrodynamics Specialist Conference. San Diego, CA, 2014.
- ⁸⁶Misra, G. and Sanyal, A.K., “Analysis of Orbit-Attitude Coupling of Spacecraft Near Small Solar System Bodies,” AIAA 2015-1777, AIAA Guidance, Navigation, and Control Conference. Kissimmee, Florida 2015.
- ⁸⁷Wilcox, B.H., et al., “Testbed for Studying the Capture of a Small, Free-Flying Asteroid in Space,” AIAA 2015-4583, AIAA SPACE 2015 Conference and Exposition. Pasadena, California, 2015.
- ⁸⁸Urrutxua, H., et al., “Temporarily Captured Asteroids as a Pathway to Affordable Asteroid Retrieval Missions,” *Journal of Guidance, Control, and Dynamics*, 2015 38:11, 2132-2145.
- ⁸⁹Brophy, J. and Oleson, S. “Spacecraft Conceptual Design for Returning Entire Near-Earth Asteroids,” AIAA 2012-4067, 48th AIAA/ASME/SAE/ASEE Joint Propulsion Conference & Exhibit. Atlanta, Georgia, 2012.
- ⁹⁰Hoyt, R.P. and James, K., “WRANGLER: Nanosatellite Architecture for Tethered De-Spin of Massive Asteroids,” AIAA 2015-4533, AIAA SPACE 2015 Conference and Exposition. Pasadena, California, 2015.
- ⁹¹Van Zandt, J.R., “Tethered Asteroids,” AIAA 2013-5302, AIAA SPACE 2013 Conference and Exposition. San Diego, CA, 2013.
- ⁹²Jones, T.C., Dorsey, J. and Doggett, W.R., “Structural Sizing Methodology for the Tendon-Actuated Lightweight In-Space Manipulator (TALISMAN) System,” AIAA 2015-4627, AIAA SPACE 2015 Conference and Exposition. Pasadena, California, 2015.
- ⁹³Bandyopadhyay, S., Chung, S. and Hadaegh, F. “Attitude Control and Stabilization of Spacecraft with a Captured Asteroid,” AIAA 2015-0596, AIAA Guidance, Navigation, and Control Conference. Kissimmee, Florida, 2015.
- ⁹⁴Parness, A., et al., “Maturing Microspine Grippers for Space Applications through Test Campaigns,” AIAA 2017-5311, AIAA SPACE and Astronautics Forum and Exposition. Orlando, FL, 2017.
- ⁹⁵Flores-Abad, A. and Crespo, L.G., “A Robotic Concept for the NASA Asteroid-capture Mission,” AIAA 2015-4584, AIAA SPACE 2015 Conference and Exposition. Pasadena, California, 2015.
- ⁹⁶James, W.W, et al., “Robotic Asteroid Prospector (RAP) NIAC Phase 1 Results,” AIAA 2014-0500, 7th Symposium on Space Resource Utilization. National Harbor, Maryland, 2014.
- ⁹⁷Dorsey, J. and Jones, T.C., “Flexible Multi-Body Dynamic Modeling of a Tendon-Actuated Lightweight In-Space MANipulator (TALISMAN),” AIAA 2015-4629, Cornelia Altenbuchner, AIAA SPACE 2015 Conference and Exposition. Pasadena, California, 2015.
- ⁹⁸Reeves, D.M., et al., “Proximity Operations for the Robotic Boulder Capture Option for the Asteroid Redirect Mission,” AIAA 2014-4433, AIAA SPACE 2014 Conference and Exposition. San Diego, CA, 2014.
- ⁹⁹Dorsey, J., et al., “Application of a Novel Long-Reach Manipulator Concept to Asteroid Redirect Missions,” AIAA 2015-0225, 2nd AIAA Spacecraft Structures Conference. Kissimmee, Florida, 2015.
- ¹⁰⁰Little, J.M. and Choueiri, E., “Electric propulsion system scaling for asteroid capture-and-return missions, AIAA 2013-4125, 49th AIAA/ASME/SAE/ASEE Joint Propulsion Conference. San Jose, CA, 2013.
- ¹⁰¹Mazanek, D.D., et al., “Asteroid Redirect Robotic Mission: Robotic Boulder Capture Option Overview,” AIAA 2014-4432, AIAA SPACE 2014 Conference and Exposition. San Diego, CA, 2014.

Asteroid Mining

- ¹⁰²Evans, T. H., et al., “Robotic Ultrasonic Pulse Velocity Sensing for Planetary Material Characterization and Exploration Objectives,” AIAA 2017-0195, 10th Symposium on Space Resource Utilization. Grapevine, Texas, 2017.
- ¹⁰³Goodman, D.M., et al., “The Robotic In-situ Surface Exploration System for Space Exploration Objectives,” AIAA 2016-5535, AIAA SPACE 2016. Long Beach, California, 2015.
- ¹⁰⁴Mueller, R.P., et al., “Opportunities and Strategies for Testing and Infusion of ISRU in the Evolvable Mars Campaign,” AIAA 2015-4459, AIAA SPACE 2015 Conference and Exposition. Pasadena, California, 2015.
- ¹⁰⁵Zacny, K. et al., “Asteroid Mining,” AIAA 2013-5304, AIAA SPACE 2013 Conference and Exposition. San Diego, CA, 2013.
- ¹⁰⁶Bazzocchi, M. and Emami, M.R., “A Systematic Assessment of Asteroid Redirection Methods for Resource Exploitation,” AIAA 2015-1181, 8th Symposium on Space Resource Utilization. Kissimmee, Florida, 2015.
- ¹⁰⁷Brophy, J., “Technology for a Robotic Asteroid Redirect Mission and Its Extensibility to Future Human and Robotic Missions,” presented at the IEEE Aerospace Conference, Big Sky, MT, 2015.
- ¹⁰⁸Hopkins, M. A., King, L.B., “Performance Characteristics of a Magnesium Hall-effect Thruster,” IEPC-2011-147, Presented at the 32nd International Electric Propulsion Conference, Wiesbaden, Germany, September 11 – 15, 2011.

Planetary Defense

¹⁰⁹Committee to Review Near-Earth Object Surveys and Hazard Mitigation Strategies, National Research Council, *Defending Planet Earth: Near-Earth Object Surveys and Hazard Mitigation Strategies*, (2010).

¹¹⁰Lu, E. T., and Love, S. G., “Gravitational Tractor for Towing Asteroids,” *Nature (London)*, Vol. 438, No. 7065, 2005, pp. 177–178.

¹¹¹Mazanek, D.D., et al., “Enhanced Gravity Tractor Technique for Planetary Defense,” IAA-PDC-15-04-11, presented at the 4th IAA Planetary Defense Conference—PDC 2015 13-17 April 2015, Frascati, Roma, Italy.

¹¹²Mazanek, D.D., et al., “Enhanced Gravity Tractor Derived from the Asteroid Redirect Mission for Deflecting Hypothetical Asteroid 2017 PDC, IAA-PDC-17-05-09, 5th IAA Planetary Defense Conference – PDC 2017, 15-19 May 2017, Tokyo, Japan

¹¹³Kitamura, S., “Large Space Debris Reorbiter Using Ion Beam Irradiation,” IAC-10-A6.4.8, 61st International Astronautical Congress, September 2010.

¹¹⁴Bombardelli, C., et al., “The ion beam shepherd: A new concept for asteroid deflection,” presented at the 2011, IAA Planetary Defense Conference, 09-12 May 2011.

¹¹⁵Bombardelli, C., et al., “Mission Analysis for the Ion Beam Deflection of Fictitious Asteroidj 2015 PDC,” presented at the 4th IAA Planetary Defense Conference—PDC 2015 13-17 April 2015, Frascati, Roma, Italy.

¹¹⁶Bombardelli, C., et al., “Deflection fo Fictitious Asteroid 2017 PDC: Ion Beam vs Kinetic Impactor,” IAA-PDC-17-05-16, 5th IAA Planetary Defense Conference – PDC 2017, 15-19 May 2017, Tokyo, Japan

¹¹⁷Brophy, J.R., “Advanced Solar Electric Propulsion for Planetary Defense,” IEPC-2015-64, Presented at Joint Conference of 30th International Symposium on Space Technology and Science, 34th International Electric Propulsion Conference and 6th Nano-satellite Symposium, Hyogo-Kobe, Japan, July 4 – 10, 2015

¹¹⁸Brophy, J., et al., “Characteristics of a High-Power Ion Beam Deflection System Necessary to Deflect the Hypothetical Asteroid 2017 PD,” IAA-PDC-17-04-03, 5th IAA Planetary Defense Conference – PDC 2017, 15-19 May 2017, Tokyo, Japan

¹¹⁹Boslough, M., Brown, P. and Harris, A., “Updated Population and Risk Assessment for Airbursts from Near-Earth Objects (NEOs),” 2.1203, 36th IEEE Aerospace Conference, Big Sky, MT, Mar 7-14, 2015.