

Next-Generation Power and Sensor Technologies: A New Perspective on Dual Space-Terrestrial Applications

presented at

2018 IDTechEx Show! Berlin

Off Grid Energy Independence

Berlin, Germany

Dr. Terry J. Hendricks, P.E., ASME Fellow[1]

[1] Technical Group Supervisor, Thermal Energy Conversions Applications & Systems Group

Jet Propulsion Laboratory, California Institute of Technology

Pasadena, California, USA

11 April 2018

Copyright 2018 California Institute of Technology. U.S. Government sponsorship acknowledged.

AGENDA

- Recent Spacecraft Power Systems
- Terrestrial Energy Recovery Applications
  - Motivations
  - New Emerging TE Materials
  - High Power Density TE Module Technology
- High Temperature Solar Photovoltaics
- Biosensor Technologies
- Final Thoughts

NASA Science Exploration Missions Need for Both Solar & Radioisotope Power Systems (RPS)

Solar power systems serve a *critical role* in the scientific exploration of the near-Earth solar system

- Moderate power levels up to 100 kW
- Operations dependent on distance and orientation with respect to Sun

Radioisotope power systems (RPS) serve a *critical role* in the scientific exploration of the deep-space solar system

- Low to moderate power levels (~100 W - 1 kW) for more than several months
- Operations independent of distance and orientation with respect to Sun



Inherent limitation of solar power



Best candidates for maximizing specific power





Multi-Mission RTG

Overview of a Radioisotope Power System

- **High grade heat produced from natural alpha (α) particle decay of Plutonium (Pu-238)**
  - 87.7-year half-life
  - Heat source temperature ~ 1300 K
- **Portion of heat energy converted to electricity via passive or dynamic thermal cycles (6%-35%)**
  - Thermoelectric (existing & under development)
  - Stirling (under development)
  - Thermophotovoltaic, Brayton, etc. (future candidates)
- **Waste heat rejected through radiators or a portion can be used for thermal control of spacecraft subsystems**



GPHS-Radioisotope Thermoelectric Generator (RTG)



Performance characteristics

- Specific power (W/kg) → Direct impact on science payload
- T/E efficiency → Reduces PuO_2 needs
- Power output → Supports diverse mission profiles

RTGs used successfully on 27 spacecrafts since 1961

- 11 Planetary (Pioneer 10 & 11, Voyager 1 & 2, Galileo, Ulysses, Cassini, New Horizons)
- 8 Earth Orbit (Transit, Nimbus, LES)
- 5 Lunar Surface (Apollo ALSEP), 3 Mars Surface (Viking, MSL/Curiosity)

CASSINI Spacecraft to Saturn (October 15th, 1997 to September 15th, 2017)

- Vastly Updated Science on Saturn's Rings
- Incredible Science on Saturn's Moon Titan
  - **Many Earth-Like Processes**
  - Liquid Rivers & Lakes of Ethane & Methane Over Frozen Water
  - Salty Brine Ocean Under Icy Crust
  - Liquid Water and Ammonia Ocean ~100km Below Frozen Crust
- Likewise, Saturn's Moon Enceladus
  - **Liquid Water Beneath its Icy, Snowy Crust**
  - Geologic Activity – Ice & Water Crystal Plumes at its South Pole





RTG Power Made this All Possible
SiGe TE Materials



CASSINI Spacecraft to Saturn (1997-2017)

- Liquid Rivers & Lakes of Ethane & Methane Over Frozen Water
  - Ethane and Methane "Rains" in Atmosphere (Pressure Slightly Higher than ~1 atm)
  - Methane Atmosphere ~5% Methane – Geologic Processes Replacing Methane
- Flew Cassini spacecraft into Saturn on 15 September 2017 (Final Dive)
  - **Grand Finale** - 22 passes between ~2500-km gap between inner rings / Saturn's upper atmosphere
  - Velocity during inner ring passages 121,000-126,000 kmph
  - RTG Power Degradation shown below – 32% over 20 years
  - Lost Cassini signal 1400 km above clouds



Fig. 1. Cassini recorded power output telemetry data over the entire mission between launch and EOM. The data is divided into four mission phases: The Venus-Earth gravity assist, the cruise to Saturn, orbiting Saturn



62º Orbit Inclination







RTG Power Made this All Possible
SiGe TE Materials

New Horizons to Pluto (2006-Continuing)

Heart of Pluto

With Love,
Pluto

476,000 miles from Pluto

Large region of jumbled, broken terrain



Vast, Icy Plain – Sputnik Planum
50,000 miles from Pluto

300 mile wide image, smallest features 0.5 mile wide



10,000 miles from Pluto

RTG Power Made this All Possible
SiGe TE Materials

Water ice hills are floating in a sea of frozen Nitrogen

New Generation of "Mature" Advanced TE Materials

Large performance gains over heritage PbTe & Si-Ge alloys



Next Generation RTG Technologies
Remaining Challenges for Achieving Low Power Degradation Rates



ATEC Segmented Module Technology Advancement

LaTe composites have starting particle sizes of 80 nm – 150 nm range, and after synthesis process it increases to submicron – 10's of microns in finished bulk

Alternate interconnect material(s)

Hot shoe with dielectric layer (modules)

Mechanically robust & chemically stable, hot side interface for 14-1-11 Zintl and composites

Strengthening and stable TE properties for 14-1-11 Zintl and composites

Mechanically compliant, high electrical/thermal conduction segment interfaces



Mechanically robust hot side interface for $La_{3-x}Te_4$ and composites

Strengthening and stable TE properties for $La_{3-x}Te_4$ composites

Aerogel thermal insulation / sublimation suppression

Cold shoe with dielectric layer (cantilevered devices, modules)

Development needed

In progress

POWER TECHNOLOGIES APPLICABLE TO SOLAR SYSTEM EXPLORATION MISSION CONCEPTS AS OF 2015(1)

Prefer low power consuming scientific instruments/sensors



MERCURY

SOLAR
- Orbiters
- Landers
- Rovers

RPS
- Polar Landers
- Long-lived Landers

BATTERIES
- Short-lived Landers

VENUS

SOLAR
- Orbiters
- Upper Atmosphere Probes*
- Surface Probes**

RPS
- Current RPS not operable in Venus surface environment

BATTERIES
- Atmospheric probes
- Surface Missions

MOON

SOLAR
- Orbiters
- Landers
- Rovers

RPS
- Polar Landers
- Long-lived Landers

BATTERIES
- Short-lived Landers

MARS

SOLAR
- Orbiters
- Landers
- Rovers

RPS
- Long-lived Polar Lander
- Long-lived, high capability rovers

BATTERIES
- Short-lived surface missions

ASTEROIDS

SOLAR
- Sample Return
- Flybys/Tours
- Orbiters
- Landers

RPS
- May be necessary for Trojan asteroids

BATTERIES
- Short-lived surface missions

JUPITER

SOLAR
- Orbiters
- Flybys

RPS
- High capability orbiters
- Long-lived moon landers

BATTERIES
- Atmospheric Probes
- Short-lived landers

SATURN

SOLAR
- Flyby s/c
- Orbiters

RPS
- High-capability orbiter
- Ring observer
- Titan Montgolfier (MMRTG)
- Long-lived surface mission

BATTERIES
- Atmospheric probes
- Short-lived surface missions

URANUS

SOLAR
Not likely to be practical

RPS
- Orbiters
- Flybys

BATTERIES
- Atmospheric probes

NEPTUNE

SOLAR
Not likely to be practical

RPS
- Orbiters
- Flybys
- Long-lived Triton Lander

BATTERIES
- Atmospheric probes

KUIPER BELT

SOLAR
Not likely to be practical

RPS
- Orbiters
- Flybys
- Landers

BATTERIES
- Short-Lived landers

*requires technology development for solar cells in corrosive environment
**requires technology development for high temperature

Solar
RPS
Primary Battery

(1) Notional mission applicability based on expert opinion developed in JPL A-Team study in August, 2015

Pre-Decisional Information — For Planning and Discussion Purposes Only

Imagine, Innovate, "Instigate" to Real-World Applications

[1]

39,000 m Up at Edge of Space
Mach 1.25

Looks Like Space to Me!!

[1]

So Talking About Dual-Use Technologies …..

[1] http://en.wikipedia.org/wiki/Felix_Baumgartner
http://www.youtube.com/watch?v=FHtvDA0W34I

United States Energy Flow



- Waste Heat To Be "Harvested"

  59.4 Quads

- Up ~ 5Quads From 2009

Source: LLNL 2015. Data is based on DOE/EIA-0035(2015-03), March, 2014. If this information or a reproduction of it is used, credit must be given to the Lawrence Livermore National Laboratory and the Department of Energy, under whose auspices the work was performed. Distributed electricity represents only retail electricity sales and does not include self-generation. EIA reports consumption of renewable resources (i.e., hydro, wind, geothermal and solar) for electricity in BTU-equivalent values by assuming a typical fossil fuel plant "heat rate." The efficiency of electricity production is calculated as the total retail electricity delivered divided by the primary energy input into electricity generation. End use efficiency is estimated as 65% for the residential and commercial sectors 80% [illegible] industrial sector, and 21% for the transportation sector. Totals may not equal sum of components due to independent rounding. LLNL-MI-410527

Environmental Effects Are Strongly Tied to Our Energy Use

- ~1 kg of CO_2 produced per 1 kWhr (Coal Produced Power)
- ~0.5 kg of CO_2 is produced for 1 kWhr (Natural Gas Power)

Down ~400 Million Metric Tons From 2008
Mostly from Reduced Coal & Petroleum Use



Industrial Process Energy Recovery Projects

- Project Goals are Often Tied to:
  - Energy Savings
  - Environmental Savings and Impacts
- Critical Peripheral Benefits Also Surface Beyond These Savings
  - Improved Product Quality (PACCAR Kenworth)
  - Improved Safety (Less Indoor Air Pollution)
  - Enhanced Product Throughput Due to Process Efficiency Increases
  - Enhanced Operational Efficiency (Less Water Use)
- Challenges:
  - Scaling Up to Industrial Processing Energy Flows
  - System Cost and Payback
  - Integrating into Industrial Processes Without Adversely Impacting Product Quality and Critical Metrics
  - High-Temperature Materials – Durability and Operational Maintenance
    - La_{3-x} Te_4 , Zintls, Skutterudite TE Materials are One Solution
  - In Some Cases, Similar Source Temperature and Energy Flow Variability as in Automobile Applications
  - "Occupied" Volume and Compactness
    - JPL Working on Higher Power Density TE Solutions in Automotive and DARPA Programs



Terrestrial Waste Energy Recovery

- Thermoelectric Systems Considered a Prime Energy Recovery Technology Candidate / Option in Many Terrest
- Terrestrial Energy Recc o:
  - Energy Savings
  - Environmental Savings anc
  - Maximizing Conversion Ef
  - Maximum Power Output
- However, JPL is Curren signs Where the Critical Design Metric is Maximizing S
  - Knowing Its Relations ficiency Points is Key
  - T_{exh} = 823 K; T_{amb} = 2
- In Addition, Key Barrie mance Anymore as System-Level Cost (As Discussed in 2015 ICT, Dresden, Germany)



High Performance, High Power Flux Skutterudite TE Module Technology



Cost Modeling and Integrating Cost Modeling With System-Level Performance Modeling is Critical

High Power Density TE Module Technology

- All-skutterudite module technology demonstrated
- High efficiency TE module demonstrated
- High Power ➡ High Power Density TE module demonstrated
- Highest power density demonstrated to date
- Exactly what is needed for various terrestrial energy recovery applications





JPL is ready to work with industry to commercialize this technology

High Temperature Photovoltaics for Venus Atmosphere

Objective: Development of a Low-intensity high-temperature (LIHT) solar cells that can function and operate effectively in the Venus atmosphere (~300ºC and 100-300 W/m^2 solar irradiance conditions).

Simplified cross-section schematic of a GaInP/GaAs 2J solar cell designed for high temperature operation.





External Quantum Efficiency (EQE) measurement of a solar cell (Top junction and Bottom junction) between room temperature and 300ºC

And did I mention it has to survive at 465ºC too!!

JPL test capability simulates Venus temperature conditions

Current-voltage (IV) measurement of a solar cell between room temperature and 300ºC



Solar cell modeling under the atmospheric conditions of Venus used to guide the ideal solar cell structure design – Current density matching of both layers

GaInP/GaAs 2J solar cells have initially shown promising performance under high temperature characterization

Grandidier et al., (2018) "**Solar Cell Analysis Under Venus Atmosphere Conditions**", 2018 45th Solar Photovoltaic Specialist Conference, Waikoloa, HI. In Preparation

Potential Missions for Venus Explorations

- Extreme environments
  - Not habitable for human
  - Very hot environment (465^{o}C)
  - Sulfuric acid environment
- Venus' high surface temperature overheat solar cells & electronics in spacecraft in a short time
- Potential Venus Missions – Aerial and Surface Missions
  - Venus Design Reference mission
  - Venus Climate Observer (planet C) – Japan Aerospace Exploration Agency (JAXA)
  - Venus Express – European Space Agency (ESA)
- Want to determine what is there
  - Surface Heat Fluxes
  - Strong magnetic fields
  - Possible life in the extremely hot environment?



Image of the planet taken by the Pioneer Venus Orbiter in 1979



Examples of Venus aerial and surface mission concepts



Computer Simulated Global View of Venus

Biosensors - What is NASA/JPL Looking For?

The answers to these questions:

- Is there life elsewhere in the Universe?
- What is the future of life on Earth and beyond?

NASA's Habitable Worlds Program

- To identify the potentially habitable environments in the Solar System and beyond
- To explore the possibility of extant life beyond the earth
- Established the NASA Astrobiology Institute (NAI) to develop the field of astrobiology and provide scientific framework for future planetary exploration missions

"When it comes to extraterrestrial life, no longer is the main question whether bodies like Mars or the outer Solar System's icy moons could be habitable. Rather, researchers have moved on to determining how they can find evidence of life, past or present, through the presence of bio-signatures and other techniques." …… Astrobiology Science Conference (AbSciCon) 2017

Extreme Environments



Extreme environmental conditions for planetary missions (e.g., temperatures, gravity, thermal shock, radiation, and chemical attack)

Habitable Worlds Program
Solar System Exploration Missions
(Follow the Water)

MARS 2020 Scientific Instruments

Mission Objectives

- Seek signs of habitable conditions and microbial life on Mars in the ancient past
- To gather knowledge and demonstrate technologies that address the challenges of future human expeditions to Mars
- Test a method for producing oxygen from the Martian atmosphere



More advanced state-of-the-art scientific instruments

- Scanning Habitable Environments with Raman and Luminescence for Organics and Chemicals (SHERLOC) sensors
- An ultraviolet Raman and fluorescence spectrometer which will be mounted on the rover's robotic arm and will search for organics and minerals that may be signs of past microbial life

Opportunities of Scientific Instruments for a Potential Jupiter's Europa Ocean Worlds Lander



- Europa is a moon that orbits the planet Jupiter
- Europa's surface is mostly solid **water** ice
- ***Europa might be the place to look for environments where life could exist in the present day***
- Life as we know depends upon three key "ingredients"
  - Liquid **water**
  - Essential chemical elements/reactions
  - A source of energy
- **Lots of opportunities for biosensor/bioelectronics communities for a potential lander/rover mission**





Cutaway diagram of Europa's interior

Advancements in Our Scientific Instruments

Commercially available system (< 5 lbs)

Our Key Objectives

- Multi-platform ***in situ*** bio/chemical sensors on **ultra-trace (ppb)** analyte concentrations under **extreme environmental conditions**
- **Low power**
- Highly portable and scalable (**reduce the payload**)
- **Non-destructive technique**
- Fast response and short detectable reaction-time
- Targeted analytes
  - Gas sensor – hydrogen, oxygen, nitrogen, CO_2, etc.
  - Raman laser bio/chemical sensor – carbohydrates, amino acids, nucleic acids, phosphorus, iron, magnesium, sodium, etc.

Hand unit (< 2lbs)

Our Technology Development Approach





- Novel engineered nanostructured electrodes can be retrofitted into spacecraft-proven sensing platforms
  - Enhanced surface area of the substrate to **~1000 m^2/g**
  - Electrode materials:
    - Au, Ag, Cu, Pd, Pt, shape memory alloys (SMAs), Ti-based alloys, CoCr alloys, and doped or un-doped biocompatible semiconducting materials
  - Tailor the surface porosity and morphology using various techniques
  - Enhance sensitivity and selectivity

Carbon-Based Electrodes for Ultra-trace Sensitivity





Porous carbon foam block



- Vertically-aligned single-walled carbon nanotubes (SWCNTs) and graphene materials to increase the active surface area of sensing electrodes
- Applications to wide range of missions
  - Human expedition missions
    - Habitable environments
    - Future planetary exploration
  - Space exploration missions
    - *In-situ* sensing in extreme environmental conditions for planetary missions
    - Landers/rovers on Venus, Mars, icy moons of Jupiter and Saturn



Final Thoughts & Conclusions

- NASA Power System and Biosensor Development Provides Direct Technology Pathway to Terrestrial "Energy Recovery" Power Systems and Biosensor Applications
- Maybe a 10-20 Year Lag – Getting Shorter Every Year
- Terrestrial Power Has Many Similar Requirements as Spacecraft Systems
  - Cost is Always An Issue
  - Space Environments More Extreme Than Terrestrial (Hot - Venus & Cold – Mars & Beyond)
  - Terrestrial Applications Have Severe Cost & Environmental Requirements
    - Spacecraft Power System Materials in Large Quantities in Earth-Based Applications Can Sometimes Cause Severe Issues on Earth
    - System Costs Generally Need to approach $1-3/W to be Competitive – TE WHR Power System Costs are Often Heat Exchanger Driven
  - JPL's latest advancements in high-power-density TE module technology & high performance heat exchangers trying to address needs
- Biosensor technology based on nanopillars and nanoporous structures
- Goal is to Transition Terrestrial Technology Advances Back into NASA Missions & Systems



Learn from the mistakes of others. You won't live long enough to make them all yourself.

Yogi Berra

Catch This Wave …… And **Ride** It!!

We Can Do This!! We Have the Tools and Knowledge!

This Too Can Be The Ride of Our Lives!!

AN ENERGY TSUNAMI AHEAD

ACKNOWLEDGMENTS

This work was carried out at the Jet Propulsion Laboratory, California Institute of Technology, under a contract to the National Aeronautics and Space Administration.

Thank you for your interest and attention

Some People See the World as It Is and Ask Why…… I Dream What Has Never Been and Ask Why Not? Robert F. Kennedy, 1968

Questions & Discussion



BACKUP SLIDES

* Methane is the world's most abundant hydrocarbon. It's the major component of natural gas and shale gas and, when burned, is an effective fuel. But it's also a major contributor to climate change, with 24 times greater potency as a greenhouse gas than carbon dioxide.

Thermoelectric Power Generation

Thermoelectric Couple



Thermoelectric effects are defined by a coupling between the electrical and thermal currents induced by an electric field and a temperature gradient

Dimensionless Thermoelectric Figure of Merit, ZT

$$ZT = \frac{\sigma S^2 T}{\lambda} = \frac{S^2 T}{\rho \lambda}$$

Seebeck coefficient S
Electrical conductivity σ
Electrical resistivity ρ
Thermal conductivity λ
Absolute temperature T



Conversion Efficiency

Power generation
(across 1275 to 300 K)
State-Of-Practice materials:
$ZT_{average}$ ~ 0.5

State-Of-the-Art materials:
$ZT_{average}$ ~ 1.1

Best SOA materials:
ZT_{peak} ~ 1.5 to 2.0

Common TE Materials:
Bi_2Te_3 300 K – 525 K
PbTe-based 400 K – 775 K
SiGe-based 525 K – 1273 K
Skutterudites 475 K – 875 K
$La_{3-x}Te_4$/Zintls 625 K – 1273 K

Conversion efficiency is a direct function of ZT and ΔT

Voyager – Interstellar Mission (1977)

- Launched 37 Years Ago
- Traveled Farther than Anyone, or Anything, in History – 11 billion miles from Earth Now
  - First Spacecraft to Travel Beyond Our "Solar Wind"
- First Flyby Studies of Jupiter, Saturn, Saturn's rings, and the Larger Moons of the Two Planets, Neptune, Uranus
  - Discovered 3 of Jupiter's Moons – Adrastea, Metis, and Thebe
  - Detailed Investigation of Saturn's Rings
- Now in Interstellar Space Outside our Solar System
- RTG Power System (Based on Si-Ge Thermoelectric Materials)
  - Still Operating and Powering Spacecraft



MARS SCIENCE LABORATORY (2012)

- Landed the Curiosity Rover on Mars in 2012 – Sky Crane
- About the Size of a Small Car (~2000 lbs)
- Radioisotope-Driven Thermoelectric Generator (RTG) Used to Power Curiosity
- Spent the Last 2 Years Investigating the Geology on Mars
- 1st Year on Mars - Discovered Strong Evidence of Prior Water on Mars
  - 3.5 Billion Years Ago We Think Mars Had Rivers, Lakes, & "Oceans"
  - Theory – Lost Its Magnetic Field & Atmosphere was Ultimately Destroyed
- Spent Last Year "Driving" from Landing Site to Mt. Sharp
  - 3-mile High Martian Mountain
  - Currently in the Foothills of Mt. Sharp
- Geology on Mars Similar to Earth



RTG Power With Heritage TE Materials Made this All Possible
TAGS, PbSnTe, PbTe TE Materials – Segmented Elements

NASA's Mars Science Laboratory

- Landed the Curiosity Rover on Mars in 2012 - Sky Crane
- About the Size of a Small Car (~2000 lbs)
- Radioisotope-Driven Thermoelectric Generator (RTG) Used to Power Curiosity

- Curiosity set out to find out if Mars ever had the right environmental conditions to support small life forms (microbes)

- Curiosity's *in situ* scientific tools found chemical and mineral evidence of past habitable environments (Rivers, Lakes, & "Oceans") on Mars



Cameras:
- Mast Camera (MastCam), Mars Hand Lens Imager (MAHLI), Mars Descent Imager (MARDI)

Spectrometers:
- Alpha Particle X-ray spectrometer (APXS), Chemistry and Camera complex (ChemCam), Chemisrty and Mineralogy (CheMin), Sample Analysis at Mars (SAM)

Radiation Detectors:
- Radiation assessment detector (RAD), Dynamic Albedo of Neutrons (DAN)

Environmental Sensors:
- Rover Environmental Monitoring Station (REMS)

Atmospheric Sensors:
- Mars Science Laboratory Entry Descent and Landing Instrument (MEDLI)

SPACECRAFT SOLAR SYSTEMS
INTERNATIONAL SPACE STATION & DAWN & JUNO

- Solar Photovoltaic Power System Used to Power Current International Space Station
  - Silicon
  - Eight 375 m^2 Solar Arrays, 84 – 120 kW
- Dawn Spacecraft
  - Asteroid Chasing - Vesta and Ceres Asteroids
  - Hyper-efficient Ion-Propulsion (Xenon fueled)
  - 10 kW of Solar Power @ 1 A.U.; 1.3 kW @ 3 A.U.
  - InGaP/InGaAs/Ge Triple Junction PV Cells (35.4 m^2)
  - Low Intensity, Low Temperature PV Effects Considered (Emerging)
- Juno Spacecraft
  - Launched to Jupiter in July 2011
  - Arrives July 2016
  - Study Jupiter Atmosphere, Magnetic, & Gravity Fields





U.S. National Waste Energy Recovery

- **Transportation Sector**
  - 12.5 Quads
  - Light-Duty Passenger Vehicles + Light-Duty Vans/Trucks (SUVs)[1]
  - Medium & Heavy-Duty Vehicles[1]

- **Industrial Process Sector is Another Opportunity**
  - 5-10 Quads of Waste Energy Flows in Industrial Processes
    - Aluminum, Glass
    - Paper
    - Petroleum
    - Chemical
  - 1.8 Quads Recoverable, Potentially 1.56 GW[2]
  - Wide Range of Temperatures & Heat Sources

- **Europe and Asia Have Similar Challenges**

Waste Energy All Around Us

[1] *Transportation Energy Data Book*, 2010, Edition 29, U.S. Department of Energy, Office of Energy Efficiency and Renewable Energy, Vehicles Technology Program. ORNL-6985, Oak Ridge National Laboratory, Oak Ridge, Tennessee. http://cta.ornl.gov/data/index.shtml.

[2] U.S. Energy Information Agency, 2007 Annual Energy Outlook

The Magnitude of Our Energy Problem

Office of Heavy Vehicle Technologies

	1973	1997
U.S.	74 Quads	91 Quads
World	225 Quads	365 Quads

2014
~98.3 Quads[1]

[1]U.S. Energy Information Agency



$16.5B @ $50/Barrel

Reference - Dr. James Eberhardt
DOE – Office of Vehicle Technologies

1 Quad of energy is equivalent to 340,000 tank cars of crude oil stretched from Miami to Seattle (3,300 miles).

Thermoelectrics in a Ford Lincoln MKT & BMW Series 6 (May 2012)

- Demonstrated 450 W Power Output on a BMW Drive Cycle at 130 kph
- Demonstrated 300 W Power Output on a Ford Lincoln MKT at 65 mph



- BMW ultimately interested in average power over NEDC
- Ford and U.S. Auto Companies ultimately interested in US06 & SC03





Drive cycle contained in UN/ECE Regulation 101

http://www1.eere.energy.gov/vehiclesandfuels/pdfs/merit_review_2012/adv_combustion/ace080_lagrandeur_2012_o.pdf



https://www1.eere.energy.gov/vehiclesandfuels/

Low-Power Energy Harvesting Systems for Outer Planets Mission Concepts

⇨**Outer Planets exploration activities**

- Through ice, water, cryogenic liquids, hot gases, high g loads, moderate to high radiation
- Such as for Europa landers, Titan explorers, Comet sample return vehicles…

⇨**Need for miniaturized robust power sources**

- To enable/prolong planetary exploration, to permit novel/more science measurements
- To enable development of novel miniaturized autonomous probes such as drop-off penetrators, weather microstations, communication relay devices, etc…



Molecular Modeling and Atomistic Simulations Supporting Electrochemical Biosensors



- JPL and academia collaborative efforts are underway to develop critical chemical/physical mechanisms in support of developing electrochemical sensor technologies
  - Bulk transport properties
  - Interfacial electrode/electrolyte properties
  - Charge-transfer properties